		BLAST RESISTANT DOOR DATA SHEET	
		APPROVED BY:	
		DATE:	
		D: MARK NUMBER 1:	SALES ORDER: ITEM:
37 : 1723 : 3 : 12 : 1 : 1 : 1 : 1 : 1 : 1 : 1 : 1 :			ADDITIONAL MARKO.
GREENSBURG, PA 15601-0070			
TELEPHONE: (724) 834-7300 FAX: (724) 830-2871			·
TAX. (724) 830-2871			
SECURE AREA (INTERIOR)		DOOR INFORMATION	VISION LIGHT INFORMATION
		MODEL NUMBER:	NO VISION LIGHTS REQUIRED
LHR CO RHR CO LH C RH		NUMBER OF LEAFS:	(J) VISION LIGHT WIDTH: "
And The Kill		DOOR SWING:	(K) VISION LIGHT HEIGH
PUBLIC AREA (EXTERIOR) or (KEY SIDE)		MATERIAL:PRIMER:	(M) VERTICAL CL:
SWING		(N) CENTER LINE (A.F.F.):	GLASS PROVIDED BY: OVERLY OTHERS
<u>MAXIMUM LIGHT</u> SIZES WITH U.L. FIRE LABEL		CENTER LINE BASED ON:	FRAME INFORMATION
3 HOUR - NO LIGHT		LEVER DEVICE STRIKE	FRAME CONFIGURATION:
1½ HOUR - 100 in.² ¾ HOUR - 1296 in.²	SI WA SLIP - IN WRAP AROUND	CROSS BAR LOCK MFG STD	FRAME ANCHORAGE:
	SLIF - IIN WKAP AROUND	NOTE: If no choice is selected, the center line will be based on manufacturer's specifications.	(A) JAMB OPENING WIDTH:
10"	FRAME CONFIGURATION		(B) JAMB OPENING HEIGHT: "
		FIRE RATING No Label	(C) JAMB DEPTH: " (D) WALL THICKNESS: "
10"+ + +10"	1	UL LABEL: 3 HR 1-1/2 HR 3/4 HR 20 MIN UL PROCEDURE: UL10B UL10C N/A	(E) JAMB TRIM:
	ੈਂ≅ੀit ±		(F) HEAD TRIM:
~~~		SILL INFORMATION	ROUGH OPENING: "
	SIDE JAMB HEAD JAMB	SILL CONDITION:	WALL TYPE:
Larger sizes are available with the use of Firelite glass - contact the		UNDERCUT: "	MASONRY/CMU CHANNEL/TUBE STEEL
factory for more information		BLAST INFO  DIRECTION: SEATING UNSEATING	
MINIMUM STILES	FRAME PROFILE	<u>-</u>	
. 5"		STATIC: LOAD: REBOUND:	DEFLECTION:
<b>←</b> A → Ŭ	→ L ←	PEAK PRESSURE:psi DURATION:	ms STANDOFF:ft
<b>I</b> ↑	<u>                                   </u>	IMPULSE:psi*ms FRAGMENT?:	
EQUAL	K	EDGE ROTATION:deg VELOCITY:	
		EQUIVALENT TNT:Ibs MATERIAL:	
	<del>     </del>	HARDW	VARE By: Overly Others
EQUAL	MI		
*	* *		
10"			
FRAME ELEVATION	DOOR ELEVATION	4	
		ADDITIONAL NOTES:	
		UNSEATING VIDEO A	
		T FLOOR	
CF-WLD CF-BLT WELD-IN BOLT-IN	NMA EWA NEW EXISTING	UN ORTILE UN	IDERCUT UNDERCUT UNDERCUT
FRAME CHANNEL IRON	MASONRY WALL ANCHOR ANCHOR	BLAST	
		VCT VCT SILL	FLUSH SILL RAISED THRESHOLD
		SEATING . ***BOTTOM LINE	DENOTES BOTTOM OF FRAME AT ALL CONDITIONS***
FRAME ANCHORAGE		BLAST DIRECTION	SILL CONDITION  SALD-003 REV# 5 (06/28/05)