| | BUI | BULLET RESISTANT WOOD DOOR DATA SHEET UL LEVELS 1-3 | |
|---|------------------------------|---|---|
| | CUSTOMER: | | APPROVED BY: |
| DOOR COM | | | |
| | 200/(101) | D: MARK NUMBER 1: | |
| 574 WEST OTTERMA | IN SIREEI | J. WARK NOWBERT. | |
| GREENSBURG, PA 15 | | | |
| TELEPHONE: (724) 834-7300 FAX: (724) 830-2871 | | | |
| TAX. (724) 650-2671 | | | |
| SECURE AREA (INTERIOR) | | DOOR INFORMATION | VISION LIGHT INFORMATION |
| | | NUMBER OF LEAFS: | NO VISION LIGHTS REQUIRED |
| LHR C RHR C LH RH | | DOOR SWING: | (J) VISION LIGHT WIDTH: |
| | | (N) CENTER LINE (A.F.F.): | (K) VISION LIGHT HEIGHT: |
| PUBLIC AREA (EXTERIOR) or (KEY SIDE) | | CENTER LINE BASED ON: | (M) VERTICAL CL: |
| SWING | | LEVER DEVICE STRIKE | |
| MAXIMUM LIGHT SIZES | | CROSS BAR LOCK MFG STD NOTE: If no choice is selected, the center line will be based | |
| NOTE: NO VISION LIGHTS WITH U.L. FIRE LABELS | | on manufacturer's specifications. | NOTE: All UL level 1-3 BR wood doors come factory glazed. |
| WITH O.E. TINE EXBEES | SI WA | UL 752 LEVEL | |
| 8 " | SLIP - IN WRAP AROUND | LEVEL 1 LEVEL 2 LEVEL 3 | FRAME INFORMATION |
| | FRAME CONFIGURATION | FIRE RATING | FRAME MATERIAL: |
| 8"+ + 8" | <u>+</u> , | UL LABEL: 20 MIN No Label | FRAME PRIMER:FRAME CONFIGURATION: |
| <u> </u> | | UL PROCEDURE: UL10C | FRAME ANCHORAGE: |
| | THE HEAD JAMB | NOTE: No vision lights allowed with U.L. fire labels. | (A) JAMB OPENING WIDTH: |
| | SIDE JAMB | SILL INFORMATION | (B) JAMB OPENING HEIGHT: |
| MINIMUM STILES | FRAME PROFILE | SILL CONDITION: | (C) JAMB DEPTH: |
| MINIMOM STILLS | TRAFFE PROFILE | UNDERCUT: " | (D) WALL THICKNESS: " (E) JAMB TRIM: " |
| ← A→ 3 | → L ← | VENEER INFORMATION | (F) HEAD TRIM: " |
| ↑ • | ↓ | VENEER: | ROUGH OPENING: " |
| EQUAL | K | FINISH: | WALL TYPE: |
| | | CUT: | METAL STUD * WOOD STUD |
| | | VENEER MATCHING: | MASONRY/CMU CHANNEL/TUBE STEEL |
| EQUAL | M T | ASSEMBLY MATCHING: | *SPLIT AND EWA ONLY: Wood blocking must be placed behind metal studs. |
| | N N | FSC/COC REQUIRED? | <u> </u> |
| * 11 11 11 | <u>* * </u> | HARDW | WARE By: Overly Others |
| 10" | | | |
| FRAME ELEVATION DOOR ELEVATION | | | |
| | | | |
| I I 4 == | _h 5 | | |
| | | | |
| | | | |
| CF-WLD NN | → ←───────── MA CF-BLT | | |
| WELD-IN NE | W BOLT-IN | ADDITIONAL NOTES: | |
| FRAME MASC ANCI | | | |
| | 1 5 | | 5 E |
| 1 | ₩ + h | NINDE ROCUT | UNDERCUT |
| | 4U 111 | FLOOR OR TILE | NDE NOE |
| | | | J <u> </u> |
| EWA SPL | LIT NSA | VCT CPT | FS TRS |
| EXISTING SPLIT FI WALL ANCHOR | RAME NEW STUD WALL ANCHOR | VCT SILL CARPETED OPENING | FLUSH SILL RAISED THRESHOLD |
| | | ***BOTTOM LINE DENOTES BOTTOM | |
| FRAME AN | <u>ICHORAGE</u> | SILL CON | DITION ENGD-256 REV# 2 (11/02/21) |
| | | | LINOD-230 INLV# 2 (11/02/21) |