	■ B	BULLET RESISTANT METAL DOOR DATA SHEET UL LEVELS 1-8	
CUSTOMER:		APPROVED BY:	
EGGATION.			
3/4 WLST OTTERMAN STREET		MARK NUMBER 1:	
GREENSBURG, PA 15601-0070			
TELEPHONE: (724) 834-7300			
FAX: (724) 830-2871			
SECURE AREA (INTERIOR)		DOOR INFORMATION	VISION LIGHT INFORMATION
		NUMBER OF LEAFS:	NO VISION LIGHTS REQUIRED
1 LHR CO RHR CO CO		DOOR SWING:	(J) VISION LIGHT WIDTH:
LH RH		MATERIAL:	(K) VISION LIGHT HEIGHT:
PUBLIC AREA (EXTERIOR) or (KEY SIDE)		PRIMER:	(L) HORIZONTAL CL:
SWING		(N) CENTER LINE (A.F.F.):	(M) VERTICAL CL:
MAXIMUM LIGHT SIZES		CENTER LINE BASED ON:  LEVER DEVICE STRIKE	GLASS PROVIDED BY: OVERLY OTHERS
NOTE: NO VISION LIGHTS		CROSS BAR LOCK MFG STD	IF BY OTHERS, GLASS THICKNESS:
WITH U.L. FIRE LABELS		NOTE: If no choice is selected, the center line will be based	FRAME INFORMATION
8":	SI WA	on manufacturer's specifications.	FRAME CONFIGURATION:
<del>  •</del>	SLIP - IN WRAP AROUND	UL 752 LEVEL	FRAME ANCHORAGE:
( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( )	FRAME CONFIGURATION	LEVEL 1 LEVEL 5	(A) JAMB OPENING WIDTH:
8"+ + + 8"	<u>+</u>	LEVEL 2 LEVEL 6	(B) JAMB OPENING HEIGHT:
<b>©</b>	PP Fr n	LEVEL 3 LEVEL 7	(C) JAMB DEPTH:
19675	† →EI + HEAD JAMB	LEVEL 4 LEVEL 8	(D) WALL THICKNESS: "
	SIDE JAMB	FIRE RATING No Label	(E) JAMB TRIM: " (F) HEAD TRIM: "
MANAGE ES	EDAME DOCETIE	UL LABEL: 3 HR 1-1/2 HR 3/4 HR 20 MIN	ROUGH OPENING:
MINIMUM STILES	FRAME PROFILE	UL PROCEDURE: UL10C	WALL TYPE:
—A—→ 5	->  L  ←	NOTE: No vision lights allowed with U.L. fire labels.	■ METAL STUD * ■ WOOD STUD
		SILL INFORMATION	MASONRY/CMU CHANNEL/TUBE STEEL
EQUAL	K	SILL CONDITION:	*SPLIT AND EWA ONLY: Wood blocking must be
		UNDERCUT:	placed behind metal studs.
	│ <del>│</del> <del>─</del> <del>│</del>	HARDW	VARE By: Overly Others
EQUAL M T			By. Overly Gires
	Ņ		
<u> </u>	<u> </u>		
↑ 10"		-	
FRAME ELEVATION	DOOR ELEVATION		
		<del></del>	
		ADDITIONAL NOTES:	
		ADDITIONAL NOTES.	
CF-WLD NM	A CF-BLT		
WELD-IN NE\ FRAME MASO			
ANCH			
		(P) (P)	1945 L
Η '	<b>т</b> + Һ	VINYL ~~ \$ ~~ \$	
	<b>4</b>	VINYL STORY AND	UNDERCUT
EWA SPL	IT NSA	VCT T CPT	FS TRS
EXISTING SPLIT FF	RAME NEW STUD	VCT T CPT T  VCT SILL CARPETED OPENING	FS T TRS T  FLUSH SILL RAISED THRESHOLD
WALL ANCHOR	WALL ANCHOR	***BOTTOM LINE DENOTES BOTTOM OF FRAME AT ALL CONDITIONS***	
FRAME AN	CHORAGE	SILL CON	DITION
			SALD-004 REV# 8 (04/21/20)