



For Immediate Release

Regarding: UL Fire-Rating Up To 45 Minutes for Overly Fully Operable STC 50 Wood Door

Overly Door Company, an ISO 9001 Certified Company located in Greensburg, PA, is pleased to announce that their Fully Operable STC 50 Wood Door is now UL Fire-Rated for up to 45 minutes to UL 10C Standard for Safety.

The UL-Fire Rated STC 50 Wood Acoustic Door was acoustically tested at Riverbank Acoustical Labs, Test Report TL21-241. Copies of this report are available at www.overly.com.

Features of the Overly STC 50 Wood Acoustic Door include: 2-1/4" thick; 11 lb./sq ft; Cam Lift Hinges; Overly Super "H" Door Bottom; Overly "H" Seals; Fire-resistant Edge Banded Wood Perimeter Stiles and Rails. Contact factory for additional specifications.

"A" and "AA" Grade Face Veneers are available in both FSC and Non-FSC configurations. Available finish options include unfinished, prime painted, clear, custom matched stain and plastic laminate. For full details, visit www.overly.com or email overly@overly.com.

Overly Sound Control Products have always been lead-free, asbestos-free and contain no added urea-formaldehyde.

For over 50 years, Overly Door Company has been an industry leader in the design, testing and manufacturing of Architectural Acoustic Door and Window Systems. Because of the unique manufacturing methods and patented designs, Overly Architectural Acoustic Wood and Plastic Laminate Doors are lighter weight than most comparable doors on the market.