

1512 S BATAVIA AVENUE  
GENEVA, IL 60134  
630-232-0104

An ALION Technical Center

RIVERBANK.ALIONSCIENCE.COM

FOUNDED 1918 BY  
WALLACE CLEMENT SABINE

## Test Report

SPONSOR: **Overly Door Company**  
Greensburg, PA

**Sound Transmission Loss**  
**RAL™-TL21-241**

CONDUCTED: 2021-06-23

Page 1 of 13

ON: Wood clad steel door assembly - Model STC5021241, operable

### TEST METHODOLOGY

Riverbank Acoustical Laboratories™ is accredited by the U.S. Department of Commerce, National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP) as an ISO 17025:2017 Laboratory (NVLAP Lab Code: 100227-0) and for this test procedure. The test reported in this document conformed explicitly with ASTM E90-09 (2016): "Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements." The single number rating of the specimen was calculated according to ASTM E413-16: "Classification for Rating Sound Insulation." A description of the measurement procedure and room specifications is available upon request. The transmission loss values are for a single direction of measurement. The results presented in this report apply to the sample as received from the test sponsor.

### INFORMATION PROVIDED BY SPONSOR

The test specimen was designated by the sponsor as Wood clad steel door assembly - Model STC5021241, operable. The following nominal product information was provided by the sponsor prior to testing. The accuracy of such sponsor-provided information can affect the validity of the test results.

#### Product Under Test

Components: MCL500 hinges  
Schlage D110S cylindrical lockset  
Pemko S88D25 Siliconeseal Adhesive Gasketing  
H-Seal  
Materials: Wood clad steel door assembly  
Manufacturer: Overly Door Company

### SPECIMEN MEASUREMENTS & TEST CONDITIONS

Through a full external visual inspection performed on the test specimen, Riverbank personnel verified the following specimen properties:

#### Door Frame

Materials: Metal door frame, concrete casting at perimeter  
Dimensions: Overall @ 1194 mm (47 in.) by 2413 mm (95 in.)  
Door frame @ 1016 mm (40 in.) by 2235 mm (88 in.)  
Depth: Overall @ 178 mm (7 in.)  
Door frame @ 165 mm (6.5 in.)  
Overall Weight: Frame and concrete @ 418.21 kg (922 lbs)

1512 S BATAVIA AVENUE  
GENEVA, IL 60134  
630-232-0104

An ALION Technical Center

RIVERBANK.ALIONSCIENCE.COM

FOUNDED 1918 BY  
WALLACE CLEMENT SABINE

## Test Report

Overly Door Company  
2021-06-23

RAL™-TL21-241

Page 2 of 13

### Door Stops

---

Materials: Formed metal rails with solid foam rubber gaskets/felt on one face  
Dimensions: Overall @ approximately 25.4 mm (1 in.) wide by 25.4 mm (1 in.) thick  
2 @ 2127 mm (83.75 in.) long  
1 @ 933 mm (36.75 in.) long  
Foam gasket @ 16 mm (0.625 in.) wide by 3 mm (0.125 in.) thick  
Felt @ 9.5 mm (0.375 in.) wide  
Installation: Fastened to interior faces of door frame, face with gaskets/felt oriented toward receive room, felt between gasket and frame  
Exposed faces of gaskets recessed 48 mm (1.89 in.) from outer face of door frame  
Overall Weight: 2.72 kg (6 lbs)

### Door Leaf

---

Materials: Wood exterior, with metal lockset and metal cam-lift hinges  
Dimensions: 908 mm (35.75 in.) by 2124 mm (83.625 in.)  
Thickness: 57 mm (2.25 in.)  
Installation: Suspended from jamb of door frame via three (3) hinges  
Door opens into receive room  
Overall Weight: Door leaf @ 103.65 kg (228.5 lbs)  
Hinges @ 2.72 kg (6 lbs) total  
Lockset @ 2.04 kg (4.5 lbs)

### Seals and Gaskets

---

#### Bulb Gaskets

Material: Hollow rubber gasket, teardrop bulb profile  
Dimensions: 12.7 mm (0.5 in.) wide by 6.35 mm (0.25 in.) overall depth  
Installation: Head; adhered to corner of rabbet and stop, wide end facing stop  
Hinge jamb; adhered to rabbet approximately 6.35 mm (0.25 in.) from receive side door frame face, narrow end facing stop  
Strike jamb; adhered to rabbet approximately 6.35 mm (0.25 in.) from receive side door frame face, wide end facing stop  
Overall Weight: Approximately 0.06 kg (0.125 lbs)

1512 S BATAVIA AVENUE  
GENEVA, IL 60134  
630-232-0104

An ALION Technical Center

RIVERBANK.ALIONSCIENCE.COM

FOUNDED 1918 BY  
WALLACE CLEMENT SABINE

## Test Report

Overly Door Company  
2021-06-23

RAL™-TL21-241

Page 3 of 13

### Seals and Gaskets (continued)

---

#### Door Sweep

Materials: Solid foam rubber, metal plate

Dimensions: Steel @ 851 mm (33.5 in.) long by 79 mm (3.125 in.) wide

Foam @ 914 mm (36 in.) long by 57 mm (2.25 in.) wide

Thickness: Steel @ 3 mm (0.12 in.)

Foam @ 24 mm (0.94 in.)

Installation: Foam adhered to plate; plate fastened to bottom edge of door leaf

Foam fits flush with source room face of door leaf via matching routed channel in door leaf

Foam protrudes approximately 6.35 mm (0.25 in.) from bottom face of door leaf

Thin layer of grease applied to foam

Overall Weight: 1.59 kg (3.5 lbs)

*Note: The specimen was fully opened and closed five (5) times immediately prior to testing in order to demonstrate operability. No further adjustments were made to the specimen.*

1512 S BATAVIA AVENUE  
GENEVA, IL 60134  
630-232-0104

An ALION Technical Center

RIVERBANK.ALIONSCIENCE.COM

FOUNDED 1918 BY  
WALLACE CLEMENT SABINE

## Test Report

Overly Door Company  
2021-06-23

RAL™-TL21-241

Page 4 of 13

### Overall Specimen Measurements

---

Dimensions: 1.19 m (47 in.) wide by 2.41 m (95 in.) high  
Thickness: 0.18 m (7 in.)  
Weight: 530.99 kg (1170.62 lbs)  
Overall Area: 2.881 m<sup>2</sup> (31.01 ft<sup>2</sup>)  
Mass per Unit Area: 184.31 kg/m<sup>2</sup> (37.75 lbs/ft<sup>2</sup>)

### Test Aperture

---

Opening Size: 1.22 m (4.0 ft.) by 2.44 m (8.0 ft.)  
Filler Wall: Yes  
Aperture Size: 1.02 m (40.0 in) wide by 2.24 m (88.0 in) high  
Transmission Area: 2.271 m<sup>2</sup> (24.44 ft<sup>2</sup>)  
Sealed: Entire periphery (both sides), including concrete, with dense mastic

*Note: The dimensions used to determine the transmission area exclude those of the concrete-filled frame into which the door frame was cast. Given that the transmission loss performance of massive solid partitions is expected to be considerably greater than that of operable doors, the amount of flanking sound transmission through the mastic-covered concrete is assumed to be negligible. The specimen dimensions reflect this assumption.*

### Test Environment

---

#### Source Room

Volume: 131.48 m<sup>3</sup>  
Temperature: 21.4 °C ± 0.6 °C  
Relative Humidity: 52.5 % ± 1.0 %

#### Receive Room

Volume: 178.33 m<sup>3</sup>  
Temperature: 21.9 °C ± 0.6 °C  
Relative Humidity: 50.0 % ± 0.0 %

#### Requirements

Temperature: 22° C +/- 2° C, not more than 3° C change over all tests.  
Relative Humidity: ≥ 30%, not more than +/- 3% change over all tests.



RIVERBANK ACOUSTICAL LABORATORIES IS ACCREDITED BY NVLAP (LAB CODE 100227-0) FOR ACOUSTICAL TESTING SERVICES IN ACCORDANCE WITH ISO/IEC 17025:2017 AND FOR THIS PROCEDURE. THIS REPORT MUST NOT BE USED BY THE CLIENT TO CLAIM PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY RAL, NVLAP, NIST, OR ANY AGENCY OF THE U.S. GOVERNMENT.

THIS REPORT SHALL NOT BE MODIFIED WITHOUT THE WRITTEN APPROVAL OF RAL. THE RESULTS REPORTED APPLY ONLY TO THE SPECIFIC SAMPLE SUBMITTED FOR TESTING; RAL ASSUMES NO RESPONSIBILITY FOR THE PERFORMANCE OF ANY OTHER SAMPLE.

1512 S BATAVIA AVENUE  
GENEVA, IL 60134  
630-232-0104

An ALION Technical Center

RIVERBANK.ALIONSCIENCE.COM

FOUNDED 1918 BY  
WALLACE CLEMENT SABINE

## Test Report

**Overly Door Company**  
2021-06-23

**RAL™-TL21-241**  
Page 5 of 13



Figure 1 – Specimen mounted in test opening, as viewed from receive room (left) and source room (right)



Figure 2 – Operation of specimen, as viewed from receive room; extent of perimeter mastic seal

1512 S BATAVIA AVENUE  
GENEVA, IL 60134  
630-232-0104

An ALION Technical Center

RIVERBANK.ALIONSCIENCE.COM

FOUNDED 1918 BY  
WALLACE CLEMENT SABINE

**Test Report**

**RAL™-TL21-241**

Page 6 of 13

**Overly Door Company**  
2021-06-23



Figure 3 – Seals and gaskets at strike jamb



Figure 4 – Seals and gaskets at head and hinge jamb

1512 S BATAVIA AVENUE  
GENEVA, IL 60134  
630-232-0104

An ALION Technical Center

RIVERBANK.ALIONSCIENCE.COM

FOUNDED 1918 BY  
WALLACE CLEMENT SABINE

**Test Report**

**Overly Door Company**  
2021-06-23

**RAL™-TL21-241**

Page 7 of 13



Figure 5 – Detail of door sweep configuration

1512 S BATAVIA AVENUE  
 GENEVA, IL 60134  
 630-232-0104

An ALION Technical Center

RIVERBANK.ALIONSCIENCE.COM

**Test Report**

FOUNDED 1918 BY  
 WALLACE CLEMENT SABINE

**Overly Door Company**  
 2021-06-23

**RAL™-TL21-241**  
 Page 8 of 13

TEST RESULTS


Sound transmission loss values are tabulated at the eighteen standard frequency bands. A graphic presentation of the data and additional information appear on the following pages. The precision of the transmission loss test data is within the limits set by the ASTM Standard E90-09 (2016). See Appendix A for identification of corrections applied to the reported data.

<u>FREQ.</u>	<u>TL</u>	<u>ΔTL</u>	<u>DEF.</u>	<u>FREQ.</u>	<u>TL</u>	<u>ΔTL</u>	<u>DEF.</u>
100	28	0.68	0	800	50	0.10	2
125	36	0.53	0	1000	51	0.09	2
160	37	0.89	0	1250	50	0.13	4
200	37	0.31	3	1600	53	0.13	1
250	38	0.35	5	2000	53	0.14	1
315	45	0.31	1	2500	54	0.11	0
400	47	0.30	2	3150	54	0.14	0
500	48	0.21	2	4000	55	0.13	0
630	49	0.16	2	5000	56	0.14	0


STC=50

ABBREVIATION INDEX

- FREQ. = 1/3 OCTAVE BAND CENTER FREQUENCY, Hz
- TL = TRANSMISSION LOSS, dB
- ΔTL = 95% CONFIDENCE INTERVAL FOR TL MEASUREMENTS, dB
- DEF. = DEFICIENCIES, dB BELOW SHIFTED STC CONTOUR (SUM OF DEF = 25)
- STC = SOUND TRANSMISSION CLASS

Tested by   
 Dean Victor  
 Lead Experimentalist

Report by   
 Malcolm Kelly  
 Test Engineer, Acoustician

Approved by   
 Eric P. Wolfram  
 Laboratory Manager



RIVERBANK ACOUSTICAL LABORATORIES IS ACCREDITED BY NVLAP (LAB CODE 100227-0) FOR ACOUSTICAL TESTING SERVICES IN ACCORDANCE WITH ISO/IEC 17025:2017 AND FOR THIS PROCEDURE. THIS REPORT MUST NOT BE USED BY THE CLIENT TO CLAIM PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY RAL, NVLAP, NIST, OR ANY AGENCY OF THE U.S. GOVERNMENT. THIS REPORT SHALL NOT BE MODIFIED WITHOUT THE WRITTEN APPROVAL OF RAL. THE RESULTS REPORTED APPLY ONLY TO THE SPECIFIC SAMPLE SUBMITTED FOR TESTING; RAL ASSUMES NO RESPONSIBILITY FOR THE PERFORMANCE OF ANY OTHER SAMPLE.



1512 S BATAVIA AVENUE  
 GENEVA, IL 60134  
 630-232-0104

An ALION Technical Center

RIVERBANK.ALIONSCIENCE.COM

**Test Report**

FOUNDED 1918 BY  
 WALLACE CLEMENT SABINE


**Overly Door Company**  
 2021-06-23

**RAL™-TL21-241**

Page 9 of 13

**SOUND TRANSMISSION REPORT**

Wood clad steel door assembly - Model STC5021241, operable



**STC=50**  
**OITC=40**



**TRANSMISSION LOSS**  
**SOUND TRANSMISSION CLASS CONTOUR**



RIVERBANK ACOUSTICAL LABORATORIES IS ACCREDITED BY NVLAP (LAB CODE 100227-0) FOR ACOUSTICAL TESTING SERVICES IN ACCORDANCE WITH ISO/IEC 17025:2017 AND FOR THIS PROCEDURE. THIS REPORT MUST NOT BE USED BY THE CLIENT TO CLAIM PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY RAL, NVLAP, NIST, OR ANY AGENCY OF THE U.S. GOVERNMENT.

THIS REPORT SHALL NOT BE MODIFIED WITHOUT THE WRITTEN APPROVAL OF RAL. THE RESULTS REPORTED APPLY ONLY TO THE SPECIFIC SAMPLE SUBMITTED FOR TESTING; RAL ASSUMES NO RESPONSIBILITY FOR THE PERFORMANCE OF ANY OTHER SAMPLE.

1512 S BATAVIA AVENUE  
 GENEVA, IL 60134  
 630-232-0104

An ALION Technical Center

RIVERBANK.ALIONSCIENCE.COM

## Test Report

FOUNDED 1918 BY  
 WALLACE CLEMENT SABINE

**Overly Door Company**  
 2021-06-23

**RAL™-TL21-241**  
 Page 10 of 13

### APPENDIX A: Extended Frequency Range Data

Specimen: Wood clad steel door assembly - Model STC5021241, operable (See Full Report)

*The following non-accredited data were obtained in accordance with ASTM E90-09 (2016), but extend beyond the defined frequency range of 100Hz to 5,000Hz. These unofficial results are representative of the RAL test environment only and intended for research & comparison purposes. Sampling precision observed during this procedure is reported below. Corrections are detailed in Appendix B.*

1/3 Octave Band Center Frequency (Hz)	Sound Transmission Loss (dB)	Applicable Corrections	ΔTL (Eq. A2.5) (dB)	Repeatability (dB)
31.5	35	F	1.10	1.24
40	37	F	0.92	1.44
50	31	F	0.58	0.98
63	21		0.66	2.33
80	26		0.94	1.46
100	28		0.68	0.77
125	36		0.53	1.28
160	37		0.89	1.18
200	37		0.31	0.74
250	38		0.35	0.53
315	45		0.31	0.46
400	47		0.30	0.41
500	48		0.21	0.41
630	49		0.16	0.32
800	50		0.10	0.30
1000	51		0.09	0.29
1250	50		0.13	0.15
1600	53		0.13	0.18
2000	53		0.14	0.12
2500	54		0.11	0.28
3150	54		0.14	0.23
4000	55		0.13	0.18
5000	56		0.14	0.26
6300	56		0.16	0.28
8000	56		0.15	0.67
10000	54	F	0.20	0.93
12500	49	F	0.28	1.93



RIVERBANK ACOUSTICAL LABORATORIES IS ACCREDITED BY NVLAP (LAB CODE 100227-0) FOR ACOUSTICAL TESTING SERVICES IN ACCORDANCE WITH ISO/IEC 17025:2017 AND FOR THIS PROCEDURE. THIS REPORT MUST NOT BE USED BY THE CLIENT TO CLAIM PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY RAL, NVLAP, NIST, OR ANY AGENCY OF THE U.S. GOVERNMENT.

THIS REPORT SHALL NOT BE MODIFIED WITHOUT THE WRITTEN APPROVAL OF RAL. THE RESULTS REPORTED APPLY ONLY TO THE SPECIFIC SAMPLE SUBMITTED FOR TESTING; RAL ASSUMES NO RESPONSIBILITY FOR THE PERFORMANCE OF ANY OTHER SAMPLE.

## Test Report

Overly Door Company  
2021-06-23

RAL™-TL21-241  
Page 11 of 13

### APPENDIX B: Glossary of Standardized Corrections and Adjustments

Specimen: Wood clad steel door assembly - Model STC5021241, operable (See Full Report)

<u>Mark</u>	<u>Interpretation</u>
<i>A</i>	Measured sound pressure levels in the receive room are within 10 dB of the ambient noise level at the marked frequency band. Receive room levels used to calculate Transmission Loss are corrected according to ASTM E90 Section 10.3.
<i>AA</i>	Measured sound pressure levels in the receive room are within 5 dB of the ambient noise level at the marked frequency band. Receive room levels used to calculate Transmission Loss are corrected according to ASTM E90 Section 10.3.1. Transmission Loss values calculated from levels corrected this way will be less than or equal to Transmission Loss values from a hypothetical test using the same specimen and a receive room with idealized ambient sound levels of $(-\infty)$ dB.
<i>F</i>	The reported Transmission Loss is within 10 dB of the laboratory flanking limit at the marked frequency band. The measured performance of the specimen may be limited by the performance of the laboratory building structure at this frequency band.
<i>Z</i>	The reported Transmission Loss at the marked frequency band has been corrected according to ASTM E90 Section A3.2.7 to account for possible sound transmission through the filler assembly.
<i>ZZ</i>	The reported Transmission Loss at the marked frequency band has been corrected according to ASTM E90 Section A3.2.8 to account for possible sound transmission through the filler assembly. Transmission Loss values corrected this way will be less than or equal to Transmission Loss values from a hypothetical test using the same specimen and an idealized filler assembly with a Sound Transmission Class rating of $(\infty)$ .

### APPENDIX C: Glossary of Variability Metrics

Specimen: Wood clad steel door assembly - Model STC5021241, operable (See Full Report)

$\Delta$ TL, the 95% confidence interval for reported transmission loss values, is calculated from the standard deviation of the sets of measurements for source room sound pressure level, receive room sound pressure level, and receive room sound absorption. This metric is calculated in an effort to quantify the combined influences of room geometry, microphone positioning, and other varying environmental conditions on reported results.

**Repeatability**, expressed as a 95% confidence interval, is calculated from the standard deviation of transmission loss as obtained from a set of six (6) consecutive tests conducted according to this test method by RAL on 2020-02-24. The tests were performed on a specimen composed of welded aluminum tubing, using the same test opening as used in this report. This metric provides an estimate of the variation in results that might be observed if the test were repeated with no change to the installed specimen. Note that repeatability will vary with the construction type.

1512 S BATAVIA AVENUE  
 GENEVA, IL 60134  
 630-232-0104

An ALION Technical Center

RIVERBANK.ALIONSCIENCE.COM

## Test Report

FOUNDED 1918 BY  
 WALLACE CLEMENT SABINE

**Overly Door Company**  
 2021-06-23

**RAL™-TL21-241**  
 Page 12 of 13

### **APPENDIX D: Determination of Outdoor Indoor Transmission Class (OITC)**

Specimen: Wood clad steel door assembly - Model STC5021241, operable (See Full Report)

The determination of the Outdoor Indoor Transmission Class (OITC) as reported below was made with explicit conformity to the procedures described in the ASTM E1332-16 test standard. Test Method ASTM E90-09 (2016) was used to obtain the sound transmission loss data. This rating is based on an average transportation noise source spectrum and an A-weighted sound level reduction, either of which may be inappropriate for some applications.

One-third Octave Band Center Frequency, Hz	Reference Sound Spectrum, dB	Test Specimen Transmission Loss, dB
80	103	26
100	102	28
125	101	36
160	98	37
200	97	37
250	95	38
315	94	45
400	93	47
500	93	48
630	91	49
800	90	50
1000	89	51
1250	89	50
1600	88	53
2000	88	53
2500	87	54
3150	85	54
4000	84	55

*OITC = 40*

1512 S BATAVIA AVENUE  
GENEVA, IL 60134  
630-232-0104

An ALION Technical Center

RIVERBANK.ALIONSCIENCE.COM

FOUNDED 1918 BY  
WALLACE CLEMENT SABINE

## Test Report

**RAL™-TL21-241**

Page 13 of 13

**Overly Door Company**

2021-06-23

### **APPENDIX D: Instruments of Traceability**

Specimen: Wood clad steel door assembly - Model STC5021241, operable (See Full Report)

<b><u>Description</u></b>	<b><u>Model</u></b>	<b><u>Serial Number</u></b>	<b><u>Date of Certification</u></b>	<b><u>Calibration Due</u></b>
System 2	Type 3160-A-042	3160-106974	2020-08-13	2021-08-13
Bruel & Kjaer Mic And Preamp D	Type 4943-B-001	2311440	2020-09-30	2021-09-30
Bruel & Kjaer Pistonphone	Type 4228	2781248	2020-08-12	2021-08-12
EXTECH Hygro 662	SD700	A083662	2020-12-18	2021-12-18
EXTECH Hygro 663	SD700	A083663	2020-12-18	2021-12-18

### **APPENDIX E: Revisions to Original Test Report**

Specimen: Wood clad steel door assembly - Model STC5021241, operable (See Full Report)

<b><u>Date</u></b>	<b><u>Revision</u></b>
2021-06-30	Original report issued

---

END



RIVERBANK ACOUSTICAL LABORATORIES IS ACCREDITED BY NVLAP (LAB CODE 100227-0) FOR ACOUSTICAL TESTING SERVICES IN ACCORDANCE WITH ISO/IEC 17025:2017 AND FOR THIS PROCEDURE. THIS REPORT MUST NOT BE USED BY THE CLIENT TO CLAIM PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY RAL, NVLAP, NIST, OR ANY AGENCY OF THE U.S. GOVERNMENT.

THIS REPORT SHALL NOT BE MODIFIED WITHOUT THE WRITTEN APPROVAL OF RAL. THE RESULTS REPORTED APPLY ONLY TO THE SPECIFIC SAMPLE SUBMITTED FOR TESTING; RAL ASSUMES NO RESPONSIBILITY FOR THE PERFORMANCE OF ANY OTHER SAMPLE.